

Commercial & Industrial Bag Filters

Purion Product Guide





Contents

| Ba | ag Filters | 1 |
|----|--|---|
| | COMMERCIAL & INDUSTRIAL #2 BAG FILTERS | 1 |
| | C&I BAG SERIES | 2 |
| | 7HP CARTRIDGE SERIES | 3 |
| | 7BEC CARTRIDGE SERIES | 4 |

Please note: Images in this product guide may vary and are a representation only. If you have any questions, please contact us for further information.



COMMERCIAL & INDUSTRIAL #2 BAG FILTERS

BAG CLAMP & SWING BOLT CLOSURES ACCEPTS #2 SIZE (7" x 32" FILTER BAGS



BAND CLAMP LID CLOSURE



SWING BOLT LID CLOSURE

| CDE CUE LO LE COLU | Model | | | | | | | |
|----------------------------------|---|--|-------------------------|--|--|--|--|--|
| SPECIFICATION | WTBFH2 -304SS-CC | WTBFH2 -316SS-CC | WTBFH2 -304SS-SB | WTBFH2 -316SS-SB | | | | |
| Material | 304SS | 316LSS | 304SS | 316SS | | | | |
| Closure | Band | Clamp | Swi | Swing Bolt | | | | |
| Number of Bags | | | 1 | | | | | |
| Bag Size | | #2 (7" x 32") - (| 178mm x 813mm) | x 813mm) | | | | |
| Perforated Basket Bag Support | 304SS 316LSS | | 304SS | 316SS | | | | |
| Outside Finishing | Mirror Polish | | | | | | | |
| Inlet/Outlet | 50mm FBSP | 2" ANSI150 6" Flange 4 bolt, 0.75" holes 4.75" PCD | 50mm FBSP | 2" ANSI150 6" Flange 4 bolt, 0.75" holes 4.75" PCD | | | | |
| Vent & Gauge | Sup | plied with 1/4" vent valv | e, pressure gauge and f | ittings | | | | |
| Filter Base | Stainless Steel, adjustable height, 3 Leg - bolt down | | | | | | | |
| Overall Height | Adjustable from 1350 to 1500mm | | | | | | | |
| Filter Body Length | 1200mm | | | | | | | |
| Footprint Diameter | t Diameter 350mm | | | | | | | |
| Operating Pressure | Pressure 7.0 bar 10.0 bar | | | | | | | |

Bag Filters - C&I Bag Series

Polypropylene & UPVC



C&I BAG SERIES

POLYPROPYLENE AND UPVC CONSTRUCTION, BAND CLAMP & SWING BOLT **CLOSURES, COMMERCIAL & INDUSTRIAL BAG FILTERS**

High flow filtration for the removal of sediment, iron precipitate, rust and heavy organics. Plastic construction for chemical resistance. Ideal for filtering paints, glues, process waters and a wide range of chemicals.



| SPECIFICATION | MODEL X100 | | | | |
|---------------------------|------------------------|--|--|--|--|
| Material | Polyethylene | | | | |
| Closure | Screw-on lid with lugs | | | | |
| Number of Bags | 1 | | | | |
| Micron Rating | 1 up to 800 | | | | |
| Flow Rates | up to 18m³/hour | | | | |
| Inlet/Outlet | 2" FBSP | | | | |
| Vent & Drain | 1/4" | | | | |
| Operating Pressure (Max.) | 7 bar | | | | |
| Bag Size | 150mm x 550mm | | | | |



| SPECIFICATION | MODEL BFHU2SB | | | | |
|---------------------------|------------------|--|--|--|--|
| Material | UPVC | | | | |
| Closure | Swing Bolt | | | | |
| Number of Bags | 1 | | | | |
| Flow Rates | Up to 40 m³/hour | | | | |
| Finishing | PVC | | | | |
| Inlet/Outlet | 2" BSPT Female | | | | |
| Vent & Drain | 1/4" | | | | |
| Operating Pressure (Max.) | 6 bar | | | | |
| Bag Size | No.2 (7"x 32") | | | | |

Bag Filters - 7HP Cartridge Series

304 & 316 Stainless Steel



7HP CARTRIDGE SERIES

304 & 316 STAINLESS STEEL CONSTRUCTION. SWING BOLT **CLOSURES, COMMERCIAL & INDUSTRIAL BAG FILTERS**



FEATURES

 304 or 316 Stainless Steel: Non coded housings. Rated to 10barG @ 110°C

Easy to Operate: Six M12 Swing bolts secure the heavy duty top cover in place

Simple Installation: 2"ANSI flanged ports as standard. Provided with leas


 Universal Fit: Suits standard DOE or Code G 65mm diameter cartridges

 Minimal Pressure Drops: Allow 10kPa for housing at max rated flow for water

 Wide Range of Liquid Applications: Fine Chemicals, Water Treatment, Pre-RO, Beverages

The 7HP all stainless steel filter housings are designed for environments where the unit will be opened frequently or where water pressure is greater than 7barG. With a sandblast finish, the 7HP is a robust yet economical answer to many filtration applications.

Options include Pressure gauges and vent valves. Buna or Viton 'O' Rings are available upon request. Sediment, Absolute Rated and Carbon cartridges are all available from Pearl Filtration.



| MODEL | NUMBER OF DOE CARTRIDGES | MAX FLOW (I/min) | A | В | С | D | O RING | FLANGE |
|-------|--------------------------------|------------------------|-----|-----|-----|------|--------|--------|
| 7HP1 | 7 X 10" | 140 | 365 | 300 | 500 | 440 | EPDM | 1.5" |
| 7HP2 | 7 X 20" | 280 | 415 | 300 | 600 | 700 | EPDM | 2" |
| 7HP3 | 7 X 30" | 420 | 415 | 300 | 700 | 960 | EPDM | 2" |
| 7HP4 | 7 X 40" | 500 | 415 | 300 | 800 | 1220 | EPDM | 2" |



Head Office

9-15 Industrial St Mackay QLD 4740 Ph: +61 7 4969 4949 Email: info@dowdens.com.au

Brisbane Office

45 Fulcrum Street Richlands QLD 4077 Ph: +61 7 3828 7000 Email: brisbane@dowdens.com.au

Rockhampton Office Proserpine Office

4/415 Yaamba Road Park Avenue QLD 4701 Ph: +61 7 4923 6969 Email: info@dowdens.com.au

2 Mann St Proserpine QLD 4800 Ph: +61 7 4969 4940 Email: info@dowdens.com.au

Bag Filters - 7BEC Cartridge Series

304 & 316 Stainless Steel



7BEC CARTRIDGE SERIES

304 & 316 STAINLESS STEEL CONSTRUCTION, V-CLAMP CLOSURES, **COMMERCIAL & INDUSTRIAL BAG FILTERS**

7BEC CARTRIDGE



FEATURES:

 304 or 316 Stainless Steel: Non coded housings. Rated to 7barG @ 110°C.

Easy to Operate: Heavy Duty V-Clamp is hand tightened for immediate access to the filter cartridges.

 Simple Installation: BSP ports as standard. Provided with floor mounting tabs.

 Universal Cartridges: fits all standard DOE or Code G 65mm diameter cartridges.

 Minimal Pressure Drops: Allow 10kPa for housing at max rated flow for water.

 Wide Range of Liquid Applications: Fine Chemicals, Water Treatment, Pre-RO. Beverages


Industrial and Commercial applications demand filtration equipment to last in their environment.

The 7BEC Series is designed to provide economical filtration, without forgetting the importance of user friendliness. For many Pre-Filtration applications, 7BEC housings are opened more frequently than downstream equipment and have to withstand frequent service use.

Options include different ports and pipe sizes, pressure gauges and vent valves.

For higher flow rates manifold systems can be fabricated locally. Sediment, Absolute Rated and Carbon cartridges are all available from Pearl Filtration.

| MODEL | NUMBER OF DOE CARTRIDGES | MAX FLOW (I/min) | A | В | С | D (mm) | O RING | BSP PORT SIZE |
|-------|--------------------------------|------------------------|-----|-----|------|-----------|--------|---------------------|
| 7BEC1 | 7 X 10" | 140 | 280 | 120 | 610 | 330 | BUNA | 2" |
| 7BEC2 | 7 X 20" | 280 | 280 | 120 | 890 | 330 | BUNA | 2" |
| 7BEC3 | 7 X 30" | 420 | 280 | 120 | 1140 | 330 | BUNA | 2" |
| 7BEC4 | 7 X 40" | 500 | 280 | 120 | 1380 | 330 | BUNA | 2" |



Head Office

9-15 Industrial St Mackay QLD 4740 Ph: +61 7 4969 4949 Email: info@dowdens.com.au

Brisbane Office

45 Fulcrum Street Richlands QLD 4077 Ph: +61 7 3828 7000 Email: brisbane@dowdens.com.au

Rockhampton Office Proserpine Office

4/415 Yaamba Road Park Avenue QLD 4701 Ph: +61 7 4923 6969 Email: info@dowdens.com.au

2 Mann St Proserpine QLD 4800 Ph: +61 7 4969 4940 Email: info@dowdens.com.au







Head Office

9-15 Industrial St Mackay QLD 4740 Ph: +61 7 4969 4949

Brisbane Office

45 Fulcrum Street Richlands QLD 4077 Ph: +61 7 4969 4949 Ph: +61 7 3828 7000
Email: info@dowdens.com.au Email: brisbane@dowdens.com.au

Rockhampton Office Proserpine Office

4/415 Yaamba Road

2 Mann St Park Avenue QLD 4701 Proserpine QLD 4800
Ph: +61 7 4923 6969 Ph: +61 7 4969 4940
Email: info@dowdens.com.au Email: info@dowdens.com.au