

HIDRO PUMP CATALOGUE

**DEWATERING
PUMPS
1000 VOLTS**

50 Hz

STANDARD


DOWDENS
PUMPING & WATER TREATMENT

Making water work for you



HIDRO pump[®]

DEWATERING STANDARD PUMPS 1000V

At Hidro Pumps, we provide expertly designed equipment that offers practical and efficient solutions for a vast range of pumping applications. Our strength lies in our ability to deliver superior technology that solves complex fluid management challenges. Every product in our portfolio is a testament to our core principles of precision, power, and innovation, ensuring you receive a reliable and high-performance solution tailored to your specific operational needs.

Our comprehensive product range are engineered to perform in the most demanding industrial environments.

Designed for robust and efficient water removal, our dewatering pumps are essential for maintaining dry and safe conditions in construction sites, mines, and municipal works. These pumps are built to handle high volumes of water, even with light abrasives, providing dependable performance when you need it most.

Products

Dewatering Pumps

Power: 1.5kW / 2hp - 11kW / 15 hp

Flow: 4l/s - 30l/s

Lift: 8m - 70m

Voltage: 1000v

Standard



Japla
HP2

Japla
HP3

Japla
HP5

Japla
HP7

Miura
HP10

Espada
HP15

Dewatering Pumps

Power: 22kw / 30hp - 335kW / 450 hp

Flow: 30ls - 250l/s

Lift: 30m - 200m

Voltage: 1000v

Standard



Diablo
HP35

Gallardo
HP58

Countach
HP80

Hurican
HP100

Aventador
HP115

Revento
HP150

Estoque
HP300

Asterion
HP450

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au



www.dowdens.com.au

INDEX

A

ASTERION HP450 STD 1000V	35
AVENTADOR HP115 SS 1000V	26, 27, 28

C

COUNTACH HP80 STD 1000V	20, 21, 22
-------------------------------	------------

D

DIABLO HP35 STD 1000V	14, 15, 16
-----------------------------	------------

E

ESPADA HP15 STD 1000V	11, 12, 13
ESTOQUE HP300 STD 1000V	32, 33, 34

G

GALLARDO HP58 STD 1000V	17, 18, 19
-------------------------------	------------

H

HURACAN HP100 STD 1000V	23, 24, 25
-------------------------------	------------

J

JALPA HP2 STD 1000V	4
JALPA HP3 STD 1000V	5
JALPA HP5 STD 1000V	6
JALPA HP7 STD 1000V	7

M

MIURA HP10 STD 1000V	8, 9, 10
----------------------------	----------

R

REVENTON HP150 STD 1000V	29, 30, 31
--------------------------------	------------

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au



www.dowdens.com.au


STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H
Power, [kW / HP]	1.8 / 2.5
Voltage, V	1000
Nominal current, A	1.6
Weight, kg	19
Max. height, mm	360
Max. width, mm	242
Discharge, in.	2"
Strainer opening Ø, mm	7



Models

H: High Pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx2.5mm² + 2x1mm², 20m^(*)

Mechanical seals

Mechanical seal in oil chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

2" H

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
External cover: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Volute: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H
Power, [kW / HP]	2.6 / 3.5
Voltage, V	1000
Nominal current, A	2.2
Weight, kg	22
Max. height, mm	370
Max. width, mm	250
Discharge, in.	2"
Strainer opening Ø, mm	7



Models

H: High Pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx2.5mm² + 2x1mm², 20m^(*)

Mechanical seals

Mechanical seal in oil chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

2" H

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
External cover: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Volute: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H
Power, [kW / HP]	3.7 / 5
Voltage, V	1000
Nominal current, A	2.9
Weight, kg	32
Max. height, mm	390
Max. width, mm	260
Discharge, in.	3"
Strainer opening Ø, mm	7



Models

H: High Pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx2.5mm² + 2x1mm², 20m^(*)

Mechanical seals

Mechanical seal in oil chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

3" H

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
External cover: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Volute: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H
Power, [kW / HP]	5.5 / 7.5
Voltage, V	1000
Nominal current, A	4.3
Weight, kg	42
Max. height, mm	425
Max. width, mm	280
Discharge, in.	3"
Strainer opening Ø, mm	7



Models

H: High Pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx4mm² + 2x1mm², 20m^(*)

Mechanical seals

Mechanical seal in oil chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

3" H

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
External cover: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Volute: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	5.5 / 7.5	5.5 / 7.5
Voltage, V	1000	1000
Nominal current, A	4.5	4.5
Weight, kg	60	60
Max. height, mm	786	786
Max. width, mm	305	305
Discharge, in.	3"	4"
Strainer opening Ø, mm	7	7



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx10mm² + 2x1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

3" H - 4" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Curve: ISO 9906

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au


ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax: 07 4969 4900
info@dowdens.com.au



H / N



VIEW CK

NOTE:
- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au

DOWDENS
PUMPING & WATER TREATMENT
Making water work for you

www.dowdens.com.au


STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	11 / 15	11 / 15
Voltage, V	1000	1000
Nominal current, A	7.9	7.9
Weight, kg	80	80
Max. height, mm	856	856
Max. width, mm	320	320
Discharge, in.	3"	4"
Strainer opening Ø, mm	7	7



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Three-phase squirrel cage motor.
Protection: IP 68

Cable

4Gx10mm² + 2x1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Deep groove ball bearing C3.

Discharge connection

3" H - 4" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au


ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au



H / N



NOTE:
- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au

DOWDENS
PUMPING & WATER TREATMENT
Making water work for you

www.dowdens.com.au


STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	22 / 30	22 / 30
Voltage, V	1000	1000
Nominal current, A	18.9	18.9
Weight, kg	180	180
Max. height, mm	1065	1065
Max. width, mm	425	425
Discharge, in.	4"	6"
Strainer opening Ø, mm	13	13



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

4Gx10mm² + 2x1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Angular contact bearing C3
Upper: Deep groove ball bearing C3

Discharge connection

4" H - 6" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Curve: ISO 9906

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
 9-15 Industrial St, Mackay Qld 4740
 Phone: 07 4969 4949 Fax: 07 4969 4900
 info@dowdens.com.au




ROCKHAMPTON
 4/415 Yaamba Rd, Rockhampton Qld 4701
 Phone: 07 4923 6969 Fax: 07 4923 6900
 info@dowdens.com.au

BRISBANE
 45 Fulcrum St, Richlands Qld 4077
 Phone: 07 3828 7000 Fax: 07 3828 7055
 brisbane@dowdens.com.au

PROSERPINE
 2 Mann St, Proserpine Qld 4800
 Phone 07 4969 4940 Fax 07 4969 4900
 info@dowdens.com.au



H / N



VIEW CK

NOTE:

- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	45 / 60	45 / 60
Voltage, V	1000	1000
Nominal current, A	32.9	32.9
Weight, kg	291	291
Max. height, mm	1336	1336
Max. width, mm	517	517
Discharge, in.	4"	6"
Strainer opening Ø, mm	12	12



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Direct / Star-Delta
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

Star-Delta: 2 Cables 4Gx10mm² + 2 x 1.5mm², 20m^(*)
Direct: 1 Cable 4Gx25mm² + 2 x 1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Double Angular contact ball bearing C3
Upper: Deep groove ball bearing C3

Discharge connection

4" H - 6" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 2 - 11

Available materials

Cover: Aluminium
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Curve : ISO 9906

Contact Your Local Dowdens Account Manager



MACKAY (Head Office)
 9-15 Industrial St, Mackay Qld 4740
 Phone: 07 4969 4949 Fax: 07 4969 4900
 info@dowdens.com.au

ROCKHAMPTON
 4/415 Yaamba Rd, Rockhampton Qld 4701
 Phone: 07 4923 6969 Fax: 07 4923 6900
 info@dowdens.com.au

BRISBANE
 45 Fulcrum St, Richlands Qld 4077
 Phone: 07 3828 7000 Fax: 07 3828 7055
 brisbane@dowdens.com.au

PROSERPINE
 2 Mann St, Proserpine Qld 4800
 Phone 07 4969 4940 Fax 07 4969 4900
 info@dowdens.com.au





VIEW CK

NOTE:

- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	52 / 70	52 / 70
Voltage, V	1000	1000
Nominal current, A	33	33
Weight, kg	649	649
Max. height, mm	1481	1481
Max. width, mm	627	627
Discharge, in.	6"	8"
Strainer opening Ø, mm	12	12



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor.
Speed: 2950 RPM
Insulation class: H
Start: Star-Delta
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables 4Gx16mm² + 2 x 1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Angular contact bearing
Upper: Cylindrical roller bearing

Discharge connection
6" H - 8" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
Cylinder: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Curve: ISO 9906

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au


ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au


PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au



H/N



VIEW CK



NOTE:

- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H
Power, [kW / HP]	60 / 80
Voltage, V	1000
Nominal current, A	52
Weight, kg	1200
Max. height, mm	1875
Max. width, mm	1053
Discharge, in.	10"
Strainer opening Ø, mm	25



Models

N: Normal Pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor, 4 poles.
Speed: 1450 RPM
Insulation class: H
Start: Star-Delta / Soft-Starter (*)
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables 4Gx25mm² + 2 x 1.5mm², 20m(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Double row ball bearing C3
Upper: Ball bearing C3

Discharge connection

10" ANSI 150 lbs.

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 6 - 11

Available materials

Cover: Cast Iron
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Casing: Cast iron
Volute: Chrome steel
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Curve: ISO 9906

Contact Your Local Dowdens Account Manager



MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





VIEW CK

NOTE:

- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	71 / 95	71 / 95
Voltage, V	1000	1000
Nominal current, A	62.7	62.7
Weight, kg	670	670
Max. height, mm	1238	1238
Max. width, mm	923	923
Discharge, in.	8"	10"
Strainer opening Ø, mm	25	25



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor 4 poles.
Speed: 1450 RPM
Insulation class: H
Start: Star-Delta / Soft Starter, VFD (*)
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables 4Gx25mm² + 2 x 1.5mm², 20m(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Double row ball bearing C3
Upper: Ball bearing C3

Discharge connection

8" H - 10" N. (*)

Limitations

Maximum submersion: 20m
Maximum liquid temperature: 40°C
Liquid pH range: 5 - 8

Available materials

Cover: Aluminium
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Housing: Aluminium
Diffusers: Aluminium + PU
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au


ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au

DOWDENS
PUMPING & WATER TREATMENT
Making water work for you

www.dowdens.com.au



Curve: ISO 9906

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
 9-15 Industrial St, Mackay Qld 4740
 Phone: 07 4969 4949 Fax: 07 4969 4900
 info@dowdens.com.au


ROCKHAMPTON
 4/415 Yaamba Rd, Rockhampton Qld 4701
 Phone: 07 4923 6969 Fax: 07 4923 6900
 info@dowdens.com.au

BRISBANE
 45 Fulcrum St, Richlands Qld 4077
 Phone: 07 3828 7000 Fax: 07 3828 7055
 brisbane@dowdens.com.au


PROSERPINE
 2 Mann St, Proserpine Qld 4800
 Phone 07 4969 4940 Fax 07 4969 4900
 info@dowdens.com.au



H / N



CN
↑



VIEW CN

NOTE:
- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	SH	H	N
Power, [kW / HP]	110 / 150	110 / 150	110 / 150
Voltage, V	1000	1000	1000
Nominal current, A	77	77	77
Weight, kg	889	889	889
Max. height, mm	1681	1681	1681
Max. width, mm	619	619	619
Discharge, in.	6"	6"	8"
Strainer opening Ø, mm	12	12	12



Models

N: Normal Pressure
H: High pressure
SH: Super high pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor, 2 poles.
Speed: 2950 RPM
Insulation class: H
Start: Star-Delta, Soft Starter
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables 4Gx35mm² + 2 x 1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Angular contact bearing
Upper: Cylindrical roller bearing

Discharge connection

6" H - 8" N. (*)

Limitations

Maximum submersion: 50m
Maximum liquid temperature: 40°C
Liquid pH range: 6 - 11

Available materials

Cover: Cast Iron
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Difusers: Cast iron + PU / High chrome steel
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au


ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au



H / N



VIEW CK

NOTE:
 - Reference Measurements
 - Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
 9-15 Industrial St, Mackay Qld 4740
 Phone: 07 4969 4949 Fax: 07 4969 4900
 info@dowdens.com.au

ROCKHAMPTON
 4/415 Yaamba Rd, Rockhampton Qld 4701
 Phone: 07 4923 6969 Fax: 07 4923 6900
 info@dowdens.com.au

BRISBANE
 45 Fulcrum St, Richlands Qld 4077
 Phone: 07 3828 7000 Fax: 07 3828 7055
 brisbane@dowdens.com.au

PROSERPINE
 2 Mann St, Proserpine Qld 4800
 Phone 07 4969 4940 Fax 07 4969 4900
 info@dowdens.com.au




STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	185 / 250	185 / 250
Voltage, V	1000	1000
Nominal current, A	133.8	133.8
Weight, kg	2400	2584
Max. height, mm	2232	2201
Max. width, mm	1111	1020
Discharge, in.	10"	10"
Strainer opening Ø, mm	16	16



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor, 4 poles.
Speed: 1450 RPM
Insulation class: H
Start: Soft Starter, VFD (*)
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables 4Gx70mm² + 2 x 1.5mm², 20m^(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Angular contact bearings
Upper: Cylindrical roller bearing

Discharge connection

H - 10" ANSI 300 lb / N - 10" ANSI 150 lb

Limitations

Maximum submersion: 50m
Maximum liquid temperature: 40°C
Liquid pH range: 6 - 11

Available materials

Cover: Cast Iron
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Difusers: Cast iron + PU / High chrome steel
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager


MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone: 07 4969 4940 Fax: 07 4969 4900
info@dowdens.com.au





Contact Your Local Dowdens Account Manager





MACKAY (Head Office)
 9-15 Industrial St, Mackay Qld 4740
 Phone: 07 4969 4949 Fax: 07 4969 4900
 info@dowdens.com.au

ROCKHAMPTON
 4/415 Yaamba Rd, Rockhampton Qld 4701
 Phone: 07 4923 6969 Fax: 07 4923 6900
 info@dowdens.com.au

BRISBANE
 45 Fulcrum St, Richlands Qld 4077
 Phone: 07 3828 7000 Fax: 07 3828 7055
 brisbane@dowdens.com.au

PROSERPINE
 2 Mann St, Proserpine Qld 4800
 Phone 07 4969 4940 Fax 07 4969 4900
 info@dowdens.com.au



**VIEW CE****VIEW Y****NOTE:**

- Reference Measurements
- Discharge on request

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)

9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON

4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE

45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE

2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au

DOWDENS
PUMPING & WATER TREATMENT
Making water work for you

www.dowdens.com.au


STANDARD



*Reference image

Electric submersible drainage pump, available in various aluminium and stainless steel alloys. For applications in mines, power plants and other industries to handle abrasive solids and water.

50 Hz	H	N
Power, [kW / HP]	335 / 450	335 / 450
Voltage, V	1000	1000
Nominal current, A	243	243
Weight, kg	3500	3250
Max. height, mm	2450	2350
Max. width, mm	1180	1180
Discharge, in.	10"	14"
Strainer opening Ø, mm	16	16



Models

N: Normal Pressure
H: High pressure

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor, 4 poles.
Speed: 1450 RPM
Insulation class: H
Start: Soft Starter, VFD (*)
Max. number of starts per hour: 12

Motor protection

Thermal contacts in the wiring.
Protection: IP 68

Cable

2 Cables Nexans RZ1K Series 4x350kcmil 3AWG, 20(*)

Mechanical seals

Double mechanical seal in oil and water chamber.
Rotary seal material: Silicon carbide
Stationary seal material: Silicon carbide
Elastomers: Viton

Bearings

Lower: Angular contact bearings
Upper: Cylindrical roller bearing

Discharge connection

*H - 10" ANSI 300 lb / N - 14" ANSI 300 lb
*H - DN250 PN40 / N - DN350 PN40

Limitations

Maximum submersion: 50m
Maximum liquid temperature: 40°C
Liquid pH range: 6 - 11

Available materials

Cover: Cast Iron
Cylinder: Carbon steel
Strainer: Carbon steel
Impeller: High chrome steel / Stainless steel
Difusers: Cast iron + PU / High chrome steel
Shaft: AISI 431 Stainless steel
Screws/Nuts: Stainless steel

This pump must be connected to an external electrical cabinet with adequate protections.

*Specifications are subject to change without notice.

Contact Your Local Dowdens Account Manager

MACKAY (Head Office)
9-15 Industrial St, Mackay Qld 4740
Phone: 07 4969 4949 Fax: 07 4969 4900
info@dowdens.com.au

ROCKHAMPTON
4/415 Yaamba Rd, Rockhampton Qld 4701
Phone: 07 4923 6969 Fax: 07 4923 6900
info@dowdens.com.au

BRISBANE
45 Fulcrum St, Richlands Qld 4077
Phone: 07 3828 7000 Fax: 07 3828 7055
brisbane@dowdens.com.au

PROSERPINE
2 Mann St, Proserpine Qld 4800
Phone 07 4969 4940 Fax 07 4969 4900
info@dowdens.com.au





Email: info@dowdens.com.au
dowdens.com.au/brands/hidro-pump



hidropump.com